




WATER DISPENSER


COUNTER MOUNT KIT

- Fresh, filtered, chilled “tap” water.
- Eliminate packaging, and disposal/recycling of glass and plastic bottles.
- Choice On Tap: ambient, chilled, chilled sparkling.
- 316 grade stainless steel.



H20-CM-KIT

 Certified by the National Sanitation Foundation

 Listed by Underwriters Laboratories

www.micromatic.com • 1 (866) 327-4159

COUNTER MOUNT KIT

Job Number: _____ Location: _____

Part No.	Description	Shipping Weight	Box Dimensions
□ H2O-CM-KIT	Counter mount water dispenser, includes water regulator and filter, CO2 regulator.	46 kg	TBD
		100 lbs	TBD

Operating Performance & Maintenance

Capacity per Hour	26 gallons
Volts	120 / 60
Dedicated Circuit Required	15 amp
Condenser HP	1/4
Plug Type	NEMA-5-15P
Approvals	UL & NSF Listed
Chiller / Carbonator Exterior	18 gauge stainless steel top, sides and back
Ventilation	Front and side ventilated
Minimum Water Inlet Pressure	30 PSI
Maximum Water Inlet Pressure	86 PSI
Minimum CO2 Inlet Pressure	37.5 PSI
Maximum CO2 Inlet Pressure	75 PSI

Pressure Set Difference Water vs CO2	8 PSI
Maximum Temperature Setting	9
Water Contact Meral	316 Grade Stainless Steel
Water Filter	1 Gallon per minute
Water Filter Composition	Synerized Activated Carbon
Full Ice Bank Capacity	Aproximately 3 hours start-up
Daily Cleaning	Clean faucets daily with food safe detergent or water/vinegar using the brush provided
6 Months Cleaning	Line Cleaning
Condenser Grills	Must be clear of dust, dirt and debris at all times

Dimensions

