



POWER PACK - WATER COOLED

PREMIUM - 2 PUMP - 7,250 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Anti-vibration pads reduce motor noise.
- Exterior sight glass to verify glycol bath level.
- Rugged stainless steel cabinet.



MMPP4305-PKG-WC

Water Cooled:

Designed for spaces with limited air circulation or high ambient temperature.



6-15P



www.micromatic.com • 1 (866) 327-4159

1 HP COMPRESSOR

Job Number: _____ Location: _____

Part No.	Description	Shipping Weight
<input type="checkbox"/> MMPP4305-PKG-WC	Water cooled power pack, 2 pump and motor	98 kg 215 lbs

Operating Performance

Compressor	1 HP	Pump Type	Rotary Vane
BTU per hour	7,250	Push In Connector	12.7mm (1/2") O.D.
Plug Type (NEMA #)	6-15P	Water Inlet & Outlet Fitting	Female 3/8" NPT
Voltage	208/230	Minimum Water Pipe Size	3/8"
Running	9.5A	Inlet Water Pressure	Minimum 40 psi / Maximum 120 psi
Refrigerant	R-134a	Water Usage	.98 GPM. Water is only used when the temperature of the condenser rises high enough to open the cooling inlet valve. This is approximately 40% of the operating time depending on ambient temperature and usage.
Charge	0.56 kg (20 oz)		
Refrigerant Running Pressure	18 (low) 140 (high)		
Bath Capacity	43.5 litre (11.5 gallons)		
Condenser Inlet Water Temperature	Minimum 45° F / Maximum 80° F		

Dimensions

