




POWER PACK - AIR COOLED

PREMIUM - 3 PUMP - 11,500 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Exterior sight glass to verify glycol bath level.
- Anti-vibration pads reduce motor noise.
- Rugged stainless steel cabinet.



MMPP4307-PKG-3



6-20P



| Part No. | Description | Shipping Weight |
|-----------------------------------------|-----------------------------------------|-------------------|
| <input type="checkbox"/> MMPP4307-PKG-3 | Air cooled power pack, 3 pump and motor | 134 kg 295 lbs |

Operating Performance

| | | | |
|--------------------|----------|------------------------------|---------------------------|
| Compressor | 1 1/2 HP | Charge | 1.04 kg (37 oz) |
| BTU per hour | 11,500 | Refrigerant Running Pressure | 55 (low) 260 (high) |
| Plug Type (NEMA #) | 6-20P | Bath Capacity | 43.5 litre (11.5 gallons) |
| Voltage | 208/230 | Pump Type | Rotary Vane |
| Running | 13A | Pump & Motors | 3 |
| Refrigerant | R-404A | Pump Motor | 1/3 HP |
| | | Push In Connector | 12.7mm (1/2") O.D. |

Dimensions

