



# POWER PACK - WATER COOLED

PREMIUM - 2 PUMP - 2,300 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Anti-vibration pads reduce motor noise.
- Exterior sight glass to verify glycol bath level.
- Rugged stainless steel cabinet.




Reverse side showing water connections.



## **MMPP4301-PKG-WC**

Water Cooled:

Designed for spaces with limited air circulation or high ambient temperature.



L5-30P



Part No.	Description	Shipping Weight
MMPP4301-PKG-WC	Water cooled power pack, 2 pump and motor	58 kg
		128 lbs

Operating Performance

<b>Compressor</b>	1/3 HP	<b>Pump Type</b>	Rotary Vane
<b>BTU per hour</b>	2,300	<b>Push In Connector</b>	12.7mm (1/2") O.D.
<b>Plug Type (NEMA #)</b>	L5-30P	<b>Water Inlet &amp; Outlet Fitting</b>	Female 3/8" NPT
<b>Voltage</b>	115	<b>Minimum Water Pipe Size</b>	3/8"
<b>Running</b>	17.2A	<b>Inlet Water Pressure</b>	Minimum 40 psi / Maximum 120 psi
<b>Refrigerant</b>	R-134a	<b>Water Usage</b>	.3 GPM. Water is only used when the temperature of the condenser rises high enough to open the cooling inlet valve. This is approximately 40% of the operating time depending on ambient temperature and usage.
<b>Charge</b>	0.34 kg (12 oz)		
<b>Refrigerant Running Pressure</b>	18 (low) 140 (high)		
<b>Bath Capacity</b>	43.5 litre (11.5 gallons)		
<b>Condenser Inlet Water Temperature</b>	Minimum 45° F / Maximum 80° F		

Dimensions

