



DIRECT DRAW DISPENSER

PRO-LINE™ 25" - 1 KEG

- Designed by beer-industry experts for performance and value.
- Low profile casters, no glass rail.
- Full-size drain tray - larger work area and improved hygiene.
- Commercial grade construction - built to last.
- Digital thermostat.



MDD23-LP-E

Black



Listed by Edison Testing Laboratories.
Conforms to UL & NSF Standards.

www.micromatic.com • 1 (866) 327-4159

PRO-LINE™ 25" - 1 KEG

Job Number: _____ Location: _____

Part No.	Finish	Doors	Shipping Weight
<input type="checkbox"/> MDD23-LP-E	Black	1	78 kg
			172 lbs

Operating Performance

Capacity of 1/2 Kegs	1	Running Amps	1.5
Cubic Feet (liters)	8.4 (239)	Voltage	115/60/1
Beer Tower Approval	NSF 7.0 and NSF 18	Plug Type	NEMA-5-15P
Approval	ETL Listed	Cord Length	8'
Compressor HP	1/10	Refrigerant	R290
Thermostat	Digital	Charge oz	2.8

Exterior	18 gauge stainless steel top, 22 gauge solid doors, 24 gauge steel front, sides and back. Black Vinyl: Front, sides.
Interior	20 gauge stainless steel floor, reinforced frame, 24 gauge galvanized walls
Ventilation	Back ventilated
Plumbing	Drain Tray: 3/4" NPT drain includes hose and drain bottle. Automatic condensate evaporator, no drain connection required. Evaporator condensate has been plumbed to a condensate pan located in the compressor housing.
Insulation	Foamed-in-place using high density, CFC-free polyurethane; 2" top, walls and floor
Casters	Standard, low profile

Dimensions

