



POWER PACK - WATER COOLED

PREMIUM - 3 PUMP - 11,500 BTUs


- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Anti-vibration pads reduce motor noise.
- Exterior sight glass to verify glycol bath level.
- Rugged stainless steel cabinet.



MMPP4307-PKG-3-WC

Water Cooled:

Designed for spaces with limited air circulation or high ambient temperature.



6-20P



www.micromatic.com • 1 (866) 327-4159

1 1/2 HP COMPRESSOR

Job Number: _____ Location: _____

Part No.	Description	Shipping Weight
<input type="checkbox"/> MMPP4307-PKG-3-WC	Water cooled power pack, 3 pump and motor	134 kg 295 lbs

Operating Performance

Compressor	1 1/2 HP	Pump Motor	1/3 HP
BTU per hour	11,500	Pump Type	Rotary Vane
Plug Type (NEMA #)	6-20P	Push In Connector	12.7mm (1/2") O.D.
Voltage	208/230	Water Inlet & Outlet Fitting	Female 3/8" NPT
Running	11.4A	Minimum Water Pipe Size	3/8"
Refrigerant	R-404A	Inlet Water Pressure	Minimum 40 psi / Maximum 120 psi
Charge	1.04 kg (37 oz)	Water Usage	.98 GPM. Water is only used when the temperature of the condenser rises high enough to open the cooling inlet valve. This is approximately 40% of the operating time depending on ambient temperature and usage.
Refrigerant Running Pressure	55 (low) 260 (high)		
Bath Capacity	43.5 litre (11.5 gallons)		
Condenser Inlet Water Temperature	Minimum 45° F / Maximum 80° F		

Dimensions

